

SAFETY DATA SHEET

MOTAQUIP CARB & THROTTLE CLEANER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	MOTAQUIP CARB & THROTTLE CLEANER
Product number	VOL407
Internal identification	B12921, 20751

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Car maintenance product. Cleaning agent.
Uses advised against	This product is not recommended for any industrial, professional or consumer use other than the identified uses stated above.

1.3. Details of the supplier of the safety data sheet

Supplier	MOTAQUIP LIMITED Unit B1, Luton Enterprise Park, Sundon Park Road, Luton Bedfordshire LU3 3GU
----------	--

1.4. Emergency telephone number

Emergency telephone	Tel:
---------------------	------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards	Aerosol 1 - H222, H229
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336 Asp. Tox. 1 - H304
Environmental hazards	Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Xi;R36/38. F+;R12. N;R51/53. R67.

Human health	In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. The product is irritating to eyes and skin. Repeated exposure may cause skin dryness or cracking.
Environmental	The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
Physicochemical	Solvent vapours may form explosive mixtures with air.

2.2. Label elements

Pictogram



Signal word

Danger

MOTAQUIP CARB & THROTTLE CLEANER

Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing vapour/spray. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/container in accordance with national regulations. P102 Keep out of reach of children.
Contains	NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT, ACETONE, PROPAN-2-OL
Detergent labelling	≥ 30% aliphatic hydrocarbons

2.3. Other hazards

The product is highly flammable.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT		30-60%
CAS number: 64742-49-0	REACH registration number: 01-2119475514-35-XXXX	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.	
Skin Irrit. 2 - H315		
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		

MOTAQUIP CARB & THROTTLE CLEANER

ACETONE		10-30%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R66 R67	
PROPAN-2-OL		10-30%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-XXXX
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R67	
BUTANE		10-30%
CAS number: 106-97-8	EC number: 203-448-7	REACH registration number: 01-2119474691-32-XXXX
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280	Classification (67/548/EEC or 1999/45/EC) F+;R12	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Keep affected person away from heat, sparks and flames. Move affected person to fresh air at once. Get medical attention if any discomfort continues. Never give anything by mouth to an unconscious person.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. Get medical attention. Show this Safety Data Sheet to the medical personnel. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place. If breathing stops, provide artificial respiration. Get medical attention.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Keep affected person under observation. Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

MOTAQUIP CARB & THROTTLE CLEANER

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	Aspiration hazard if swallowed. The fluid can enter the lungs and cause damage (chemical pneumonitis, possibly fatal). Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. Nausea, vomiting.
Skin contact	Skin irritation.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Dry chemicals, sand, dolomite etc. Alcohol-resistant foam. Carbon dioxide (CO ₂).
-------------------------------------	--

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
---------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂). Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapours may form explosive mixtures with air. Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Risk of re-ignition after fire has been extinguished. Risk of explosion. Move containers from fire area if it can be done without risk. Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material. Do not use water jet as an extinguisher, as this will spread the fire. Contain and collect extinguishing water. If risk of water pollution occurs, notify appropriate authorities. Avoid the spillage or runoff entering drains, sewers or watercourses.
---	--

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Isolate area. Keep unnecessary and unprotected personnel from entering the area. Refer to Section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.
-----------------------------	--

6.2. Environmental precautions

MOTAQUIP CARB & THROTTLE CLEANER

Environmental precautions Avoid from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Contain spillage with sand, earth or other suitable non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Ventilate well, stop flow of gas or liquid if possible. Remove ignition sources. Do not allow chemical to enter confined spaces such as sewers due to explosion risk. Sewers designed to preclude formation of explosive concentrations of vapour may be permitted. Use non sparking handtools and explosion-proof electric equipment. Absorb in vermiculite, dry sand or earth and place into containers. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13. The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See Section 12 for additional information on ecological hazards.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not wear contact lenses. Static electricity and formation of sparks must be prevented. During application and drying, solvent vapours will be emitted. Use non sparking handtools and explosion-proof electric equipment. Eye wash facilities and emergency shower must be available when handling this product. Vapours may accumulate on the floor and in low-lying areas. Contaminated rags and cloths must be put in fireproof containers for disposal. Avoid eating, drinking and smoking when using the product. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Avoid contact with oxidising agents. Keep only in the original container.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

No exposure limit value known.

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

MOTAQUIP CARB & THROTTLE CLEANER

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

Carc

The carcinogenic classification only applies if Butane contains more than 0.1% of buta-1,3-diene.

WEL = Workplace Exposure Limit

Carc = Capable of causing cancer and/or heritable genetic damage.

Ingredient comments WEL = Workplace Exposure Limits

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT (CAS: 64742-49-0)

DNEL Industry - Dermal; Long term systemic effects: >300 mg/kg/day
 Industry - Inhalation; Long term systemic effects: >2035 mg/kg/day
 Consumer - Dermal; Long term systemic effects: >699 mg/kg/day
 Consumer - Oral; Long term systemic effects: >699 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: >608 mg/m³

PNEC No PNEC available.

ACETONE (CAS: 67-64-1)

DNEL Industry - Dermal; Long term : 186 mg/kg/day
 Industry - Inhalation; Short term : 2420 mg/m³
 Industry - Inhalation; Long term : 1210 mg/m³
 Consumer - Oral; Long term : 62 mg/kg/day
 Consumer - Dermal; Long term : 62 mg/kg/day
 Consumer - Inhalation; Long term : 200 mg/m³

PNEC - Fresh water; 10.6 mg/l
 - Marine water; 1.06 mg/l
 - Sediment (Freshwater); 30.4 mg/kg sediment dw
 - Sediment (Marinewater); 3.04 mg/kg sediment dw
 - Soil; 0.112 mg/kg soil dw
 - STP; 29.5 mg/l

PROPAN-2-OL (CAS: 67-63-0)

DNEL Industry - Inhalation; Long term systemic effects: 500 mg/m³
 Consumer - Dermal; Long term systemic effects: 319 mg/kg/day
 Consumer - Oral; Long term systemic effects: 26 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 89 mg/m³
 Industry - Dermal; Long term systemic effects: 888 mg/kg/day

PNEC - Fresh water; 140.9 mg/l
 - Marine water; 140.9 mg/l
 - Intermittent release; 140.9 mg/l
 - Sediment (Freshwater); 552 mg/kg
 - Sediment (Marinewater); 552 mg/kg
 - STP; 2251 mg/l
 - Soil; 28 mg/kg

MOTAQUIP CARB & THROTTLE CLEANER

BUTANE (CAS: 106-97-8)

DNEL No DNEL available.

PNEC No PNEC available.

ISOBUTANE (CAS: 75-28-5)

DNEL No DNEL available.

PNEC No PNEC available.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. Use explosion-proof general and local exhaust ventilation.

Eye/face protection

Contact lenses should not be worn when working with this chemical. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. If hands are cut or scratched, use gloves chemically resistant to this material even for brief exposures. Use gloves with insulation for thermal protection (EN 407), when needed. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other skin and body protection

Use engineering controls to reduce air contamination to permissible exposure level. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station and safety shower.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. Do not eat, drink or smoke when using this product.

MOTAQUIP CARB & THROTTLE CLEANER

Respiratory protection	Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Colourless.
Odour	Characteristic. Organic solvents. Hydrocarbons.
Initial boiling point and range	BOILING POINT RANGE 65°C TO 95°C @ 760 mm Hg
Flash point	Below minus 15°C CC (Closed cup).
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.0
Vapour pressure	12.5 kPa @ °C
Relative density	0.714 @ 20°C
Solubility(ies)	Practically insoluble in Water. Some of the Isopropanol/Acetone may partition into Water.
Auto-ignition temperature	400°C
Viscosity	0.5 cSt @ 20°C
Comments	Information given concerns the concentrated solution.

9.2. Other information

Refractive index	1.378
Volatility	100% Highly volatile.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	No particular stability concerns. Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Will not polymerise.
---	--

10.4. Conditions to avoid

MOTAQUIP CARB & THROTTLE CLEANER

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidising agents. Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

Other health effects There is no evidence that the product can cause cancer.

General information To the best of our knowledge the chemical, physical and toxicological properties have not been thoroughly investigated.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Prolonged inhalation of high concentrations may damage respiratory system.

Skin contact Product has a defatting effect on skin. May cause skin irritation/eczema. Repeated exposure may cause skin dryness or cracking.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

Route of entry Inhalation

Toxicological information on ingredients.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,840.0

Species Rat Rat

ATE oral (mg/kg) 5,841.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,920.0

Species Rat Rat

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 23.5

MOTAQUIP CARB & THROTTLE CLEANER

Species	Rat
ATE inhalation (vapours mg/l)	23.5
<u>Skin corrosion/irritation</u>	
Animal data	Irritating.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Not classified. May cause slight transient irritation.
<u>Skin sensitisation</u>	
Skin sensitisation	Not considered to be a skin sensitizer
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Negative.
Genotoxicity - in vivo	Negative.
<u>Carcinogenicity</u>	
Carcinogenicity	The current toxicological knowledge allows to not classify the product as a carcinogen.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No evidence of reproductive toxicity in animal studies.
Reproductive toxicity - development	No evidence of reproductive toxicity in animal studies.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	No information available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	No known effects based on information supplied.
Target organs	Central nervous system
<u>Aspiration hazard</u>	
Aspiration hazard	The fluid can enter the lungs and cause damage (chemical pneumonitis, possibly fatal).
<u>Inhalation</u>	
Inhalation	Vapours may cause drowsiness and dizziness.
<u>Ingestion</u>	
Ingestion	Avoid vomiting and stomach flushing because of the risk of aspiration. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
<u>Skin contact</u>	
Skin contact	Irritating to skin.
<u>Eye contact</u>	
Eye contact	May cause temporary eye irritation.

ACETONE

MOTAQUIP CARB & THROTTLE CLEANER

Acute toxicity - oral

Acute toxicity oral (LD₅₀
mg/kg) 5,800.0

Species Rat

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀
mg/kg) 7,401.0

Species Rabbit

ATE dermal (mg/kg) 7,401.0

Acute toxicity - inhalation

Acute toxicity inhalation
(LC₅₀ vapours mg/l) 76.0

Species Rat

ATE inhalation (vapours
mg/l) 76.0

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye
damage/irritation Moderately irritating.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro : Negative.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Target organs Respiratory system, lungs Irritating to respiratory system.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 900 mg/kg, Oral, Rat

Inhalation Vapours may cause drowsiness and dizziness.

Skin contact Repeated exposure may cause skin dryness or cracking.

MOTAQUIP CARB & THROTTLE CLEANER

Eye contact	Irritating to eyes. May cause chemical eye burns.
Acute and chronic health hazards	Gas or vapour is harmful on prolonged exposure or in high concentrations. Symptoms following overexposure may include the following: Irritation of eyes and mucous membranes. Narcotic effect. A single exposure may cause the following adverse effects: Central nervous system depression. Prolonged contact may cause dryness of the skin. Prolonged or repeated exposure may cause severe irritation.
Route of entry	Skin absorption Inhalation
Target organs	Central nervous system Eyes Gastro-intestinal tract Respiratory system, lungs Skin
Medical symptoms	Irritation of eyes and mucous membranes. Upper respiratory irritation. Skin irritation.
Medical considerations	Skin disorders and allergies.

PROPAN-2-OL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,840.0

Species Rat Rat

Notes (oral LD₅₀)

ATE oral (mg/kg) 5,840.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 16.4

Species Rabbit Rabbit

ATE dermal (mg/kg) 12,874.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 25.5

Species Rat

ATE inhalation (vapours mg/l) 25.5

Skin corrosion/irritation

Animal data Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Rabbit eyes: Severe eye irritation.

Respiratory sensitisation

Respiratory sensitisation Not available.

Skin sensitisation

Skin sensitisation Not considered to be a skin sensitizer

MOTAQUIP CARB & THROTTLE CLEANER

Germ cell mutagenicity

Genotoxicity - in vitro Negative.

Genotoxicity - in vivo Negative.

Reproductive toxicity

Reproductive toxicity - fertility Does not interfere with fertility.

Reproductive toxicity - development No evidence of reproductive toxicity in animal studies.

Specific target organ toxicity - single exposure

STOT - single exposure Inhalation: May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Oral and inhalation repeated exposure studies demonstrated target organ effects in male rats (kidney) and male/female mice (thyroid) by mechanisms of action that are not relevant to humans. Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Aspiration hazard if swallowed. The fluid can enter the lungs and cause damage (chemical pneumonitis, possibly fatal).

Inhalation Drowsiness, dizziness, disorientation, vertigo.

Ingestion No specific health hazards known.

Skin contact No specific health hazards known.

Eye contact Irritating to eyes. Splashes in eyes may cause strong pain. Vapour acts as irritant.

Acute and chronic health hazards Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

BUTANE

Acute toxicity - oral

Notes (oral LD₅₀) No information available.

Acute toxicity - dermal

Notes (dermal LD₅₀) No information available.

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 658.0

Species Rat

ATE inhalation (vapours mg/l) 658.0

Skin corrosion/irritation

MOTAQUIP CARB & THROTTLE CLEANER

Animal data Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Respiratory sensitisation

Respiratory sensitisation No known effects from this product.

Skin sensitisation

Skin sensitisation No known effects from this product.

Germ cell mutagenicity

Genotoxicity - in vitro Negative.

Genotoxicity - in vivo Negative.

Carcinogenicity

Carcinogenicity No information available.

IARC carcinogenicity No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC

Reproductive toxicity

Reproductive toxicity - fertility No evidence of reproductive toxicity in animal studies.

Reproductive toxicity - development This substance has no evidence of toxicity to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard No data available.

Inhalation

In low concentrations may cause narcotic effects, dizziness, headache, nausea, loss of co-ordination and irregular cardiac activity. In high concentrations may cause loss of mobility/consciousness and it may cause asphyxiation.

SECTION 12: Ecological Information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Ecological information on ingredients.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

MOTAQUIP CARB & THROTTLE CLEANER

12.1. Toxicity

Ecological information on ingredients.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Acute toxicity - fish	LL ₅₀ , 96 hours: 11.4 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	LC ₅₀ , 48 hours: 3 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 10 mg/l, Freshwater algae
Chronic toxicity - fish early life stage	NOEC, 28 days, 28 days: 1.534 mg/l, Onchorhynchus mykiss (Rainbow trout)
Chronic toxicity - aquatic invertebrates	NOEC, 21 days, 21 days: 1 mg/l, Daphnia magna

ACETONE

Acute toxicity - fish	LC ₅₀ , 96 hours: 5540 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 8800 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: >100 mg/l, Pseudokirchneriella subcapitata
Chronic toxicity - aquatic invertebrates	NOEC, 28 days: 2212 mg/l, Daphnia magna

PROPAN-2-OL

Acute toxicity - fish	LC ₅₀ , 96 hours: 9640 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 24 hours: 9714 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours, 72 hours: > 1000 mg/l, Scenedesmus subspicatus
Acute toxicity - microorganisms	EC ₅₀ , : > 1000 mg/l, Activated sludge

BUTANE

Acute toxicity - fish	LC ₅₀ , 96 hours: 24.11 mg/l, Fish
Acute toxicity - aquatic invertebrates	LC ₅₀ , 48 hours: 14.22 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 7.71 mg/l, Freshwater algae

12.2. Persistence and degradability

Persistence and degradability The product is degraded completely by photochemical oxidation. Volatile substances are degraded in the atmosphere within a few days.

MOTAQUIP CARB & THROTTLE CLEANER

Ecological information on ingredients.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Persistence and degradability	The substance is readily biodegradable.
Biodegradation	- Degradation (%) 98: 28 days

ACETONE

Persistence and degradability	The substance is readily biodegradable.
--------------------------------------	---

PROPAN-2-OL

Persistence and degradability	The product is expected to be biodegradable.
Biodegradation	- Degradation (%) 95%: 21 days

BUTANE

Biodegradation	The substance is readily biodegradable.
-----------------------	---

12.3. Bioaccumulative potential

Bioaccumulative potential	The product contains potentially bioaccumulating substances. Accumulates in soil and sediment.
----------------------------------	--

Ecological information on ingredients.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Bioaccumulative potential	Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
----------------------------------	--

ACETONE

Bioaccumulative potential	The product is not bioaccumulating. BCF: 3,
Partition coefficient	: -0.24

PROPAN-2-OL

Bioaccumulative potential	The product is not bioaccumulating.
Partition coefficient	log Pow: 0.05

BUTANE

Bioaccumulative potential	The product is not bioaccumulating.
----------------------------------	-------------------------------------

12.4. Mobility in soil

MOTAQUIP CARB & THROTTLE CLEANER

Mobility

The product contains substances which are insoluble in water and which may spread on water surfaces. The product contains environmentally hazardous substances which are bound to particulate matter and are retained in sediments.

Ecological information on ingredients.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Mobility

Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

ACETONE

Adsorption/desorption coefficient

Soil - : 1.5 @ 20°C

PROPAN-2-OL

Mobility

The product is soluble in water.

Adsorption/desorption coefficient

Soil - Koc: ~ 1.1 @ °C

Henry's law constant

0.00000338 atm m³/mol @ 25°C

BUTANE

Mobility

No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

ACETONE

Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

PROPAN-2-OL

Results of PBT and vPvB assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

BUTANE

Results of PBT and vPvB assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

MOTAQUIP CARB & THROTTLE CLEANER

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor.

Waste class Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS (CONTAINS: NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT)

Proper shipping name (IMDG) AEROSOLS (CONTAINS: NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT)

Proper shipping name (ICAO) AEROSOLS (CONTAINS: NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT)

Proper shipping name (ADN) AEROSOLS (CONTAINS: NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT)

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ICAO subsidiary risk N/A

ADN class 2.1

Transport labels



14.4. Packing group

ADR/RID packing group None

MOTAQUIP CARB & THROTTLE CLEANER

IMDG packing group	None
ADN packing group	None
ICAO packing group	None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Emergency Action Code	N/A
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). EH40/2005 Workplace exposure limits. The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
EU legislation	Dangerous Substances Directive 67/548/EEC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	HS&E Manager.
Revision date	01/06/2015
Revision	7

MOTAQUIP CARB & THROTTLE CLEANER

Supersedes date	26/09/2014
SDS status	Approved.
Risk phrases in full	R11 Highly flammable. R12 Extremely flammable. R36 Irritating to eyes. R36/38 Irritating to eyes and skin. R38 Irritating to skin. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.