

ATF DEXRON III

1 LITRE	5 LITRE	25 LITRE
VOL425	VOL426	VOL427

PRODUCT SPECIFICATION

Description

Automatic Transmission Fluid, for use in multiple applications where Dexron IIIH is specified.

High performance automatic transmission fluid, with superior low temperature fluidity, high temperature resistance properties and improved critical component protection. Formulated to protect in the harshest of operating conditions. Advanced additive package protects against wear and rust. Specially designed, high performance automatic transmission fluid. Recommended for all applications where Dexron IIIH is specified, including but not limited to; automatic transmissions, powershift transmissions, transaxles, torque converters, hydrostatic drives, fluid couplings, fluid clutches, transfer boxes, brake boosters, levelling systems, hydraulic systems, bogie lifts, cab tilt mechanisms, motorcycle suspension forks, etc.

Note: DO NOT USE in automotive transmissions specifying Ford ESW-M2C33-F fluids.

Performance Levels

Dexron® IIIH

Ford ESP-M2C138-CJ / 166-H

Ford Mercon®

Allison TES-389

Allison TES-228 (C-4)

Physical Characteristics	
Kinematic Viscosity at 100°C, cSt.	7.1
Kinematic Viscosity at 40°C, cSt.	35.9
Viscosity Index	167
Flash Point (Closed), °C	195
Density at 15.6°C	0.858
Pour Point, °C	-51
Appearance	Red

Figures based on average production values.

TDS Oil ATF Dexron III - 25.02.19 Issue 16

